




NOTE: ALL MATERIAL COMPLIANT ROHS STANDARD

REVISION INFORMATION			
Rev.	Rev. Date	Modified By	Brief Description
	2014.08.05		

" L=50FT±15CM"



Wire



Packing

Technical Requirements

1. Electrical Characteristics:

1.1. cable must pass electrical testing, no short circuit, open circuit, indirect sexual contact, insufficient insulation, dislocation, and other electrical contact resistance of adverse circumstances

1.2 Electrical Test Conditions

Conductor Resistance: $\le 10 \Omega$
 Insulation resistance: >math>\ge 10 M\Omega / 300V</math>

2. Appearance requirements:

- 2.1 No shot short, shrink, flow liner
- 2.2 Wire surface printing clear, smooth appearance, can not have scratches and obvious color
- 2.3 15PIN connector no empty pin and blunt glue
- 2.4 Terminals can not have oxidation or electrodeposited coating fall off

3. Size request

- 3.1 cable length match the drawing
- 3.2 "A" qc test according to this size

4. cable wire connect point view the point

5. Packing:

Circle around a single package.

1). Material List :

NO.	PART NAME	SPECIFICATION DESCRIPTION	QTY	UNIT
⑤	SCREW	Screw 2.3*4.5MM	4	PCS
④	Outer Molding	PVC 45P Black	NA	KG
③	PE	PE Internal Mold Material	NA	KG
②	Connector	HD15PM Blue Bobbin Nickel-Plated	2	PCS
①	Wire	(7/0.12TC*FIVE*30/0.12CCA*2.5PVC)*0.5Cmm*7/0.12TC*9C*AL*0.7/0.12BC*1288 AL-BG ODR. 5	50	FT



DRAWN BY	DATE: 2014/08/05	DESCRIPTION: 50Ft SVGA Male to Male Cable
CHECKED BY	SHEET 1 of 1	ITEM NO. 180445
APPROVED BY	SCALE 1:1	REV. 00 UNIT: mm