


Product Specification

Vendor #:	JIANDE CITY FEILONG ELECTRICAL APPLIANCE CO.,LTD		Vendor Signature:	Shao
Item No:	215010RBK	Description:	6 Outlet Power with Surge	
Photo(s)		Color	Indent Marking based on ETL us Or equivalent standard	
		Black	C(ETL)US 3139719 TYPE SJT 3 × 2.08mm ² (14AWG) 60°C VW-1 300V FT2 FeiLong	
		Raw Material		
		Plastic:ABS 100g		
Key Features & Specs		Copper Strip:15g		
Male Blades:ETL CETL Recognized components(NEM A-5-15P)		ON / OFF Swith: with Light	Compound Requirement	
Female Contacts:ETL CETL Recognized Components(NEM A-5-15P)		Cabel:3C SJT 14AWG 12FT	PVC 60° C Insulation Compound Approved for SJT Cable	
Female Ground:ETL CETL Recognized Components(NEM A-5-15P)		Jacket Construction	Cold Bend Test Requirement	
Agency Approvals:ETL		100% Fully pressure Extruded Jacket	Must pass cold bend test at-20° C	
Rate:AC 15A 125V 60Hz 1875W				
Maximum Surge:3000A mp,6000V.90J		Included Contents	Production Time	
Test			30-40 Days	
Hipot test@1.5 k v		MOQ:2000 PCS	Payment Terms	
Power test@ with light can light		EPA / CARB: /	T/T	
Drop test @ 70 cm				
Grounded test@ with ground equirement				
ETL file #	UL file #	CSA / UL file #	FDAcl #: /	
3139719	/	/		Date: 2024/10/30